

CHEMIE_
FEUERWEHR_
ENTWÄSSERUNG_

CHEMISTRY_
FIREFIGHTER_
CITY DRAINAGE_



HL-1000-EX











Die Handleuchte HL-1000-EX ist aufgrund des **Aluminiumgehäuses** extrem robust und wird zusätzlich durch ein **Neoprencover** vor Staub und Dreck geschützt. Die **Zone 1/21 Ex-Zertifizierung** und der **IP68-Schutz** machen die Handleuchte zum perfekten **Begleiter in dunklen, feuchten und gefährlichen Zonen** aller Art. Über den ergonomischen Griff kann die Leuchte bequem durchgeschaltet werden und ein **mitgeliefertes Trageband** erlaubt ein praktisches Mitführen der Leuchte. Ein **digitales Display** im Rücken der Leuchte setzt Sie prozentgenau über den aktuellen Akkustand in Kenntnis.

The hand lamp HL-1000-EX is extremely robust due to its **aluminum housing** and is additionally protected from dust and dirt by a **neoprene cover**. The **zone 1/21 Ex-certification** and the **IP68** protection make the hand lamp the perfect **companion in dark, wet and dangerous zones** of all kinds. The ergonomic handle makes it easy to toggle through the light modes, and an **included carrying strap** allows the light to be conveniently carried around. A **digital display** in the back of the lamp informs you precisely about the current battery status.



HL-1000-EX

TECHNISCHE DATEN TECHNICAL DATA

Cree XP-G LED			Akkustandsanzeige durch Display Display for battery status indication
Cree XP-G LED			
890/515/890 Lumen			IP68
890/515/890 lumens			IP68
830/480/830 Meter			67mm x 140mm
830/480/830 meters			67mm x 140mm
Power- / Arbeits- / Blinklicht power- / working- / flashing light			900 Gramm 900 grams
8/16/20 Stunden 8/16/20 hours			<8 Stunden Ladezeit <8 hours charging duration



ATEX



II 2G Ex db ib IIC T6 Gb
II 2D Ex ib tb IIIC T80°C Db IP68
-20°C <Ta< +55°C



KS-1000-EX



SCAN FOR
DETAILS

